



Hazardous Safety Products Ltd


# HSP Quad 4.2m DCU gas, twin axle, self contained trailer (code:TRAILER0100)



HSP are proud to introduce the latest manufactured equipment within our range. The HSP Quad is fully self-contained. The HSP Quad is fitted with a petrol generator and twin water tanks so can be used in remote locations as well as on mains supply. Designed for use within the UK asbestos industry it meets all the requirements for local legislation. The unit is fitted with four showers so can cater for up to sixteen workers. The HSP Quad also meets the requirements for European Type Approval.



# Quad 4.2m DCU Self Contained Trailer



## External Features include


- Suzy cable for towing
- 4 x Corner Steadies
- Sliding Lockable Steps
- Braked tow hitch assembly
- Twin Axle – 2000kg GVW
- External Water Filling Point
- Integrated LPG Storage and connection
- Twin Integrated water filtration system & spanner – 2 x outlets
- Integrated petrol generator on sliding shelf
- Integrated fresh water pump for supply to system
- Integrated fresh water pump for filling water tank from external bowser
- Combination Door Locks
- T Bar Cupboard Locks
- Hot & Cold Water Drainage Points front & rear
- 4 x Grab Handles



## Clean Internal Features include

- 16 Lockers with power socket – lockable with padlock
- 16 Hooks
- 1 mirror
- 12V LED Lighting PIR
- Over Voltage Protection
- Water Tank Level Indicator
- Tubular Heater with guard
- Fan Heater
- Integrated Bench
- Earth Rod Holder
- LPG Room Sealed Boiler
- Electric RCD Protection
- Water Drainage Trap
- Self-closing Doors With Vents
- Easy Clean Walls & Floors





### Shower Room Features include

- Twin water tanks 250 Litre each (500 total)
- Extra Tank Filling Point Internal
- 2 x sinks
- 4 x Thermostatic Mixer Bars and shower head
- 8 x Hooks
- Mirror
- 12V Led Lighting PIR
- Waste Water Filtration Start Button (12V)
- Water Drainage Trap
- Self-closing Doors With Vents
- Easy Clean Walls & Floors



### Dirty End Features include

- Free standing Negative pressure unit with hinged transit plate
- Integrated Bench
- Tubular Heater
- 12V Led Lighting PIR
- Water Drainage Trap
- 16 x hooks
- Mirror
- Self-closing Doors With Vents
- Easy Clean Walls & Floors

## Electrical Specifications

Supply Voltage	230v @ 50/60Hz
----------------	----------------

### Mains Input Max.:

Current Draw	16A
--------------	-----

12V Led Lighting	PIR Activated
------------------	---------------

### Rinnai 50HD-LPG LPG Gas Boiler Water Heater:

Electronic Control	80 Watt
--------------------	---------

	15 litre/min
--	--------------

Approvals	CE
-----------	----

Honda Power	
-------------	--

Generator - Petrol	2.7 Kva (2.2kw)
--------------------	-----------------

Approvals	CE
-----------	----

Negative Pressure Unit	240 watt/(1.05A)
------------------------	------------------

Approvals	CE
-----------	----

### Heating:

Clean Room	1000 watt/(6 A)-Blower
------------	------------------------

Dirty Room	130 watt/(0.5A)- Tubular
------------	--------------------------

Water Supply Pump	600 watt (3A)
-------------------	---------------

Approvals	CE
-----------	----

Waste Water Pumps	200 watt- /0.95A -Each
-------------------	------------------------

Filtration Specification	2 x 25 Micron & 2x 5 Micron
--------------------------	-----------------------------

Approvals (Pump)	CE
------------------	----

## Negative Pressure Unit

Pre-filter Size	292 mm x 292 mm x 47 mm
-----------------	-------------------------

Pre-filter Efficiency	EU4
-----------------------	-----

HEPA Filter Size	305 mm x 305 mm x 117 mm
------------------	--------------------------

HEPA Filter Efficiency	0.995%
------------------------	--------

Temperature Range	0 to +45°C
-------------------	------------

Controls	On/Off Switch
----------	---------------

Protection	RCD
------------	-----

### Air Flow rate:

(DCU operating conditions)	450 m³/hr
----------------------------	-----------

## Dimensions & Weights

Body Length	4200mm
-------------	--------

Length Inc. A Frame	
---------------------	--

& Coupling	5750mm
------------	--------

Width	2075mm
-------	--------

### Overall Height:

From Ground	2590mm
-------------	--------

Gross Laden Weight	2000 kg
--------------------	---------

Un- Laden Weight	1650 kg
------------------	---------

Vertical Load On Towball	95kg
--------------------------	------

## Internal Dimensions

Dirty End	1290mm x 2000mm
-----------	-----------------

Shower Room	1400mm x 2000mm
-------------	-----------------

Clean End	1450mm x 2000mm
-----------	-----------------

Water Tank Capacity	2 x 250 Litre
---------------------	---------------

Shower Heads	4
--------------	---



**Hazardous Safety Products Ltd**  
Unit C1, New Venture Business Park  
Lamberhead Industrial Estate  
Leopold Street, Pemberton  
Wigan WN5 8DH